

C1-Pro-IP-Camera-Specifications

Model		C1 Pro	
Hardware Features	Image Sensor	1/3" CMOS Sensor	
	Display Resolution	2560x1440 (4.0 Megapixels)	
	Lens	f=4.0mm Fixed, F=2.0, with IR Cut	
	Angle of View	Horizontal: 80° Vertical: 42°	
	Pan/Tilt Angle	Horizontal: 355° Vertical: 105°	
	Minimum Illumination	0 Lux (With IR Illuminator)	
	IR Distance	12 Meters (40ft)	
	Dimension	103×95×117 mm	
	Weight	300 g	
	Power Input	5.0V/2A, <6W	
	Interface		One 10M/100Mbps RJ45
			Power Interface
		Micro SD Card Slot	
		Built-in Microphone and Speaker Reset Button	
Software Features	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P	
	Image Compression	H.264	
	Maximal Frame Rate	PAL/NTSC: 25fps	
	Code Rate	1024Kbps~8192Kbps	
	Audio	Two-Way Audio	
	Max. User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams).	
	Browser Supported	IE, Edge, Chrome, Firefox, Safari	
Wireless Features	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Record Mode	Motion Record/Schedule Record (Default: Motion Record)	
	Wireless Standard	IEEE 802.11a/b/g/n	
Wireless Features	Operating Frequency	2.4GHz/5GHz	
	Wireless Security	WPA-PSK/WPA2-PSK	
Other Parameters	Temperature	Operating Temperature: -10°C~+55°C	
		Storage Temperature: -40°C~70°C	
	Humidity	Operating Humidity: 20% ~ 85%	
		Storage Humidity: 10% ~ 90%	
Waterproof	No		