

E1-Pro-IP-Camera-Specifications		
	Model	E1 Pro
Hardware Features	Image Sensor	1/2.7" CMOS Sensor
	Display Resolution	2560x1440 (4 Megapixels)
	Lens	f=4.0mm Fixed, F=2.4, with IR Cut
	Angle of View	Horizontal: 82°
		Vertical: 43°
	Pan/Tilt Angle	Horizontal: 355°
		Vertical: 50°
	Minimum Illumination	0 Lux (with IR Illuminator)
	IR Distance	12m (40ft) (LED: 8pcs/14mil/850nm)
	Dimension	Ø76x106mm
	Weight	200g
Power Input	DC 5.0V/1A	
Interface	Power	
	Micro SD Card Slot (Max. 128GB)	
	Built-in Microphone and Speaker	
	Reset Button	
Software Features	Protocols & Standards	SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, P2P
	Image Compression	H.264
	Maximal Frame Rate	25fps (Default: 15fps)
	Code Rate	1024Kbps ~ 5120Kbps
	Audio	Two-way Audio
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
	Browser Supported	No
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Record Mode	Motion-triggered recording; scheduled recording; 24/7 recording	
Wireless Features	Wireless Standard	IEEE 802.11a/b/g/n
	Operating Frequency	2.4 GHz/5 GHz
	Wireless Security	WPA-PSK/WPA2-PSK
Other Parameters	Temperature	Operating Temperature: -10°C~+55°C
		Storage Temperature: -40°C~70°C
	Humidity	Operating Humidity: 20% ~ 85%
		Storage Humidity: 10% ~ 90%
Waterproof	No	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/