

E1-Pro-IP-Camera-Specifications		
	Model	E1 Pro
Hardware Features	Image Sensor	1/3" CMOS Sensor
	Display Resolution	2560x1440 (4 Megapixels)
	Lens	f=4.0mm Fixed, F=2.0, with IR Cut
	Angle of View	Horizontal: 80° Vertical: 42°
	Pan/Tilt Angle	Horizontal: 355° Vertical: 50°
	Minimum Illumination	0 Lux (with IR Illuminator)
	IR Distance	12 Meters (40ft) (LED: 8pcs/14mil/850nm)
	Dimension	Ø76x106mm
	Weight	200g
	Power Input	DC 5.0V/1A
	Interface	Power Interface Micro SD Card Slot Built-in Microphone and Speaker Reset Button
Software Features	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, P2P
	Image Compression	H.264
	Maximal Frame Rate	20fps (Default: 15fps)
	Code Rate	1024Kbps ~ 4096Kbps
	Audio	Two-Way Audio
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
	Browser Supported	No
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Record Mode	Motion Recording	
Wireless Features	Wireless Standard	IEEE 802.11a/b/g/n
	Operating Frequency	2.4 GHz/5 GHz
	Wireless Security	WPA-PSK/WPA2-PSK
Other Parameters	Temperature	Operating Temperature: -10°C~+55°C Storage Temperature: -40°C~70°C
	Humidity	Operating Humidity: 20% ~ 85% Storage Humidity: 10% ~ 90%
	Waterproof	No