

RLC-410W-4MP-IP-Camera-Specifications			
	Model	RLC-410W	
Video & Audio	Image Sensor	1/3" CMOS Sensor	
	Video Resolution	Default: 2560 x 1440 (4MP) @30fps	
	Lens	f=4.0mm fixed, F=2.0, with IR cut	
	Video Format	H.264	
	Field of View	Horizontal:	80°
		Vertical:	42°
	Day & Night	IR-cut filter with auto-switching	
	Night Vision	30 meters (100ft) (LED: 18pcs/14mil/850nm)	
Power	Audio	Audio recording	
	DC Power	DC 12.0V 1A, <12W	
Interface	Power	DC power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps RJ45	
	Storage	Micro SD card slot (max. 256GB)	
	Audio	Built-in microphone	
Software Features	Frame Rate	Mainstream: 2fps - 30fps (default: 15fps)	
		Substream: 4fps - 15fps (default: 7fps)	
	Code Rate	Mainstream: 1024Kbps - 8192Kbps (default: 3072Kbps)	
		Substream: 64Kbps - 512Kbps (default: 160Kbps)	
	Browsers Supported	Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Smart Alarm	Person detection; vehicle detection; motion detection	
	Recording Modes	Motion recording (default); scheduled recording; 24/7 recording	
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P		
Maximal User Access	20 users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2		
Works with	Google Assistant		
WiFi	Wireless Standard	IEEE 802.11a/b/g/n	
	Operating Frequency	2.4GHz/5GHz	
	Wireless Security	WPA-PSK/WPA2-PSK	
Working Environment	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)	
	Humidity	Operating Humidity: 10% ~ 90%	
	Waterproof	IP66	
Size & Weight	Dimension	Φ67 x 186mm	
	Weight	430g	
Warranty	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> .	