

Reolink-Go-IP-Camera-Specifications

	Model	Reolink Go
<b>Video &amp; Audio</b>	Image Sensor	Starlight CMOS Image Sensor
	Video Resolution	1080p HD at 15 frames/sec
	Video Format	H.264
	Field of View	Fixed lens, 110° diagonal
	Night Vision	Up to 10 m (33 ft)
	Digital Zoom	6x digital zoom
	Audio	High-quality speaker and microphone
<b>PIR Detection &amp; Alerts</b>	PIR Detecting Distance	Adjustable up to 10 m (33 ft)
	PIR Detecting Angle	120° horizontal
	Audio Alert	Customized voice-recordable alerts
	Other Alerts	Instant email alerts and push notifications
<b>3G/4G Bandwidth</b>	Frequency Bands	Europe: LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8  the United States: LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5
	Transmission Data	LTE FDD: Max 10Mbps (DL), Max 5Mbps (UL) LTE TDD: Max 8.96Mbps (DL), Max 3.1Mbps (UL) HSPA+: Max 42Mbps (DL), Max 5.76Mbps (UL) UMTS: Max 384Kbps (DL), Max 384Kbps (UL)
	Battery	7800mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
	Solar	Can be powered by Reolink Solar Panel
<b>Power</b>	DC Power	Can be powered by 5V/2A power adaptor
	Local Storage	Supports up to 64GB micro SD card
<b>Storage</b>	Cloud Storage	Supports Reolink Cloud
	Operating Temperature	-10° to 55° C (14° to 131° F)
<b>Working Environment</b>	Weather Resistance	Weatherproof
	Size	Ø75 x 113 mm (Ø75 x 4.4 in)
<b>Size &amp; Weight</b>	Weight (Battery included)	380 g (13.4 oz)
	Warranty	Limited Warranty
		2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>